



<https://www.nomad-aviation.com>

## Aircraft Specifications and Performance



### Sikorsky S-61 A

Max external load capacity (note 1b)  
Payload 30° C @ 1000 feet (HOGE) (note 1a/b)

5000kgs  
External load – 4000Kg  
Internal load – 3180KG  
Passengers - nil  
120knots  
14,000 feet DA  
2 pilots

Fast cruise  
Max operating altitude (note 2)  
Min crew



### Airbus 332C/L

Max external load capacity (note 1b)  
Payload 30° C @ 1000 feet (HOGE) (note1a/b)

4500gs  
External load – 4040Kg  
Internal load – 3290KG  
Passengers - 17/19  
130knots  
20,000 feet PA  
1 or 2 pilots depending on type of operation

Fast cruise  
Max operating altitude (note 3)  
Min crew

Note 1a – numbers derived are based on;

- 1 hrs fuel with a 20 min reserve,
- aircraft equipped for onshore VFR operations.

Note 1b - numbers to be used as a guide only. Actual operating environment and final aircraft configurations will effect actual payloads

Note 2 – Limit for take-off and landings is 12,000 feet DA

Note 3 - Limit for take-off is 15,000 feet PA. MAUW must be below 18410 lbs (8353kgs)